

| | | | | |
|------|-----|------|---|----------------------------------|
| IS&R | L1 | 0 | ("10565745").PN. | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L2 | 1 | "10565745" | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L3 | 1203 | 378/98.8 | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L4 | 67 | 378/98.8 and right with angle | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L5 | 22 | 378/98.8 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L6 | 9 | 378/50 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L7 | 5 | 378/51 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L8 | 0 | 378/52 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L9 | 9 | 378/53 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L10 | 10 | 378/54 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L11 | 8 | 378/55 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L12 | 26 | 378/57 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L13 | 12 | 378/68 and right with angle and target | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L14 | 2 | 378/208 and right with angle and target and detector | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L15 | 320 | x-ray and right with angle and target and two with detector | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L16 | 4 | x-ray and right with angle same target same two with detector | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L17 | 2 | 378/98.8 and right with angle same two with detector | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L18 | 73 | 378/98.8 and angle same two with detector | US-PGPUB; USPAT; USOCR; EPO; JPO |
| BRS | L19 | 1 | (x-ray and right with angle and target and two with detector and mov\$5 and position\$5).clm. | US-PGPUB |
| BRS | L20 | 1 | (x-ray and right with angle and target and two with detector and mov\$5).clm. | US-PGPUB |
| BRS | L21 | 1 | (x-ray and right with angle and target and two with detector).clm. | US-PGPUB |
| BRS | L22 | 19 | (x-ray and angle and target and two with detector).clm. | US-PGPUB |

(19) 世界知的所有権機関
国際事務局



(43) 国際公開日
2005 年1 月27 日 (27.01.2005)

PCT


(10) 国際公開番号
WO 2005/008227 A1

- (51) 国際特許分類: G01N 23/04 (72) 発明者; および
(75) 発明者/出願人 (米国についてののみ): 中井 啓介
(NAKAI, Keisuke) [JP/JP]; 〒542-0081 大阪府 大阪市
(21) 国際出願番号: PCT/JP2003/009232 中央区南船場3丁目3番27号 ポニー工業株式会
社内 Osaka (JP). 笹倉 繁 (SASAKURA, Shigeru) [JP/JP];
(22) 国際出願日: 2003 年7 月22 日 (22.07.2003) 〒542-0081 大阪府 大阪市 中央区南船場3丁目3番
27号 ポニー工業株式会社内 Osaka (JP). 鈴木 雅之
(25) 国際出願の言語: 日本語 (SUZUKI, Masayuki) [JP/JP]; 〒542-0081 大阪府 大阪
(26) 国際公開の言語: 日本語 市 中央区南船場3丁目3番27号 ポニー工業株式
会社内 Osaka (JP).
(71) 出願人 (米国を除く全ての指定国について): ポニー
工業株式会社 (PONY INDUSTRY CO., LTD.) [JP/JP];
〒542-0081 大阪府 大阪市 中央区南船場3丁目3番
27号 Osaka (JP). (74) 代理人: 北村 光司 (KITAMURA, Koji); 〒530-0047 大
阪府 大阪市 北区西天満4丁目5番14-101号 北
村光司特許事務所 Osaka (JP).

[続葉有]

(54) Title: TRANSMISSION IMAGER

(54) 発明の名称: 透過撮影装置



(57) Abstract: A transmission imager of simple structure for capturing transmission images from two or more different viewpoints. The transmission imager comprises a source device (2) for emitting radiation from a target (2a), a radiation sensor, and a specimen table which is disposed between the target (2) and the radiation sensor and on which a specimen is mounted. The radiation sensor and the target (2a) are so arranged that the central part (P) of the sensing surface of the radiation sensor is generally vertical to the reference axes (L1, L2) connecting the central part (P) and the target (2a). The radiation sensor comprises a pair of first and second radiation sensors (3, 4). The first radiation sensor (3) is moved toward/away from the target (2a) by a drive mechanism and can be disposed farther from the target (2a) than the second radiation sensor (4). The source device (2) and the first and second radiation sensors (3, 4) are so arranged that the target (2a) of the source device (2) is opposed to a cathode (2b) at an angle and the cathode (2b) is disposed on the second radiation sensor (4) side.

(57) 要約: 簡易な構成で2以上の異なる視点からの透過撮影画像を得ることの可能な透過撮影装置を提供することを目的とする。ターゲット2aから放射線を照射する線源装置2と放射線検出体とを設け、これらターゲット2及び放射線検出体の間に試料を取り付ける試料テーブルを設ける。放射線検出体の検出面の中心部Pがこの中心部Pとターゲット2

[続葉有]

WO 2005/008227 A1

Search Notes